

MD-1524 & MS-1524 Specifications

Finish: All steel components shall be thoroughly cleaned and phosphatized for rust resistance in a five-stage pre-treatment process. A high grade of polyester/epoxy powder paint is to be applied electrostatically with a gloss reading of between 55 and 65. The finish shall have a salt spray rating of 250 hours or more.

Drawers: All drawers on the MD-1524 operate on ball-bearing slides, which can be fully extended. The drawer itself consists of a body, a front with inner liner, a back panel, and two tracks for sliding compressors. The tracks contain two slides, depressed and welded into the bottom of the drawer. The unit comes standard with keylock which locks all drawers simultaneously. The entire welded assembly is paint finished with recessed pulls.

Recessed Pulls: Short pull doors on the MS-1524 are furnished with a durable black plastic recessed locking handle, with a plastic chrome frame. All short pull handles are located in the middle of the door. The entire welded assembly is paint finished.

I. Material Specifications:

MS-1524:

<u>Part Name</u>	<u>Gauge</u>
Door Latch Cam	14
Modular Door	20
Modular Door Stiffener	24
Modular Body Wrap	20
Modular Back	24
Modular Corner Angle	16
Modular 15" Shelf	22
Modular Door Frame Stiffener	20
24" Modular Bottom	24

MD-1524:

<u>Part Name</u>	<u>Gauge</u>
Door Divider	22
Drawer Body	24
Drawer Back	24
Drawer Runner	18
Drawer Front	22
Modular Drawer Stiffener	24
Modular Body Wrap	20
Modular Back	24
Drawer Upright	18
Drawer Lock Bar	14
Modular Drawer Cabinet Bottom Front Panel	22
Modular Bottom	24
Modular Drawer Spacer	20
Modular Drawer Track	18
Modular Mounting Angle	16