

File Cart Specifications

Materials: File Carts as well as all Tennsco products are fabricated of high quality, cold rolled carbon steel, free of scale or rust and fully pickled. Exposed edges, corners and surface areas are free of sharp edges and all workmanship is of the highest quality as measured by the industry.

Finish: All steel components shall be thoroughly cleaned and phosphatized for rust resistance in a five-stage pre-treatment process. A high grade of polyester/epoxy powder paint is to be applied electrostatically with a gloss reading of between 55 and 65. The finish shall have a salt spray rating of 250 hours or more.

Single or Double Entry Shelf: Shelves are constructed of 18 Gauge Steel. They have corresponding slots on 1" centers. 16 gauge End Caps are welded on each end of the shelf.

End Frame: The End Frame (HE-XX) is formed into a U shape. It is fabricated from a single length of 16 gauge 1" x 1" seam welded steel tube.

Rubber Bumper: 5" Diameter Rubber Bumpers (RD-1) are used to shield and protect the Casters. They are installed at the Open ends of the End Frames between the caster and the end of the 1" x 1" Tubing.

5" Diameter Casters: Large Diameter Polyurethane Casters (LC-1) are used to optimize the carts mobility. The Casters are made from Polyurethane with a Polyolifin Core. They have Sealed Steel Ball Bearings for years of worry free service. They have a steel shaft that is inserted into the ends of the End Frames for installation.